



SLOTLIGHT LED II

2 1/2" Recessed,
Individual

- Ideal for applications in restricted space
- 2,5", 4" or 6" aperture
- Lengths are nominal
- Opal Flush Lens
- Emergency back-up options available

SLEDI	2					P	W	DU		
FIXTURE	WIDTH	MOUNTING	LIGHT LEVEL	LED	LENGTH	OPTIC	COLOR	DRIVER	OPTIONS	ORDERING PART NUMBER
SLEDI SLOTLIGHT LED II Individual Recessed	2 2 1/2"	EA Flangeless - After Sheetrock	04 450 lm/ft	835 80 CRI, 3500 K	04 4'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025387
									EL Standby Battery Pack, Left Side	11025388
					08 8'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025399
									EL Standby Battery Pack, Left Side	11025400
					12 12'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025411
									EL Standby Battery Pack, Left Side	11025412
			07 750 lm/ft	835 80 CRI, 3500 K	04 4'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025389
									EL Standby Battery Pack, Left Side	11025390
					08 8'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025401
									EL Standby Battery Pack, Left Side	11025402
					12 12'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025413
									EL Standby Battery Pack, Left Side	11025414



SLOTLIGHT LED II

2 1/2" Recessed,
Individual

- Ideal for applications in restricted space
- 2,5", 4" or 6" aperture
- Lengths are nominal
- Opal Flush Lens
- Emergency back-up options available

SLEDI	2					P	W	DU		
FIXTURE	WIDTH	MOUNTING	LIGHT LEVEL	LED	LENGTH	OPTIC	COLOR	DRIVER	OPTIONS	ORDERING PART NUMBER
SLEDI SLOTLIGHT LED II Individual Recessed	2 2 1/2"	SG Lay-in, 9/16" Slotgrid or Tegular *	04 450 lm/ft	835 80 CRI, 3500 K	04 4'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025391
									EL Standby Battery Pack, Left Side	11025392
					08 8'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025403
									EL Standby Battery Pack, Left Side	11025404
					12 12'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025415
									EL Standby Battery Pack, Left Side	11025416
			07 750 lm/ft	835 80 CRI, 3500 K	04 4'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025393
									EL Standby Battery Pack, Left Side	11025394
					08 8'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025405
									EL Standby Battery Pack, Left Side	11025406
					12 12'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025417
									EL Standby Battery Pack, Left Side	11025418

* Lay-In fixtures compatible with Armstrong TechZone and USG Logix Ceilings



SLOTLIGHT LED II

2 1/2" Recessed,
Individual

- Ideal for applications in restricted space
- 2,5", 4" or 6" aperture
- Lengths are nominal
- Opal Flush Lens
- Emergency back-up options available

SLEDI	2					P	W	DU		
FIXTURE	WIDTH	MOUNTING	LIGHT LEVEL	LED	LENGTH	OPTIC	COLOR	DRIVER	OPTIONS	ORDERING PART NUMBER
SLEDI SLOTLIGHT LED II Individual Recessed	2 2 1/2"	IW Lay-in, 15/16" Tee *	04 450 lm/ft	835 80 CRI, 3500 K	04 4'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025395
									EL Standby Battery Pack, Left Side	11025396
					08 8'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025407
									EL Standby Battery Pack, Left Side	11025408
					12 12'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025419
									EL Standby Battery Pack, Left Side	11025420
			07 750 lm/ft	835 80 CRI, 3500 K	04 4'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025397
									EL Standby Battery Pack, Left Side	11025398
					08 8'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025409
									EL Standby Battery Pack, Left Side	11025410
					12 12'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025421
									EL Standby Battery Pack, Left Side	11025422

* Lay-In fixtures compatible with Armstrong TechZone and USG Logix Ceilings