



**4" Recessed Individual**



# SLOTLIGHT LED II

- Ideal for applications in restricted space
- 2,5", 4" or 6" aperture
- Lengths are nominal
- Opal Flush Lens
- Emergency back-up options available

SLEDI	4					P	W	DU		
FIXTURE	WIDTH	MOUNTING	LIGHT LEVEL	LED	LENGTH	OPTIC	COLOR	DRIVER	OPTIONS	ORDERING PART NUMBER
SLEDI SLOTLIGHT LED II Individual Recessed	4 4'	EA Flangeless - After Sheetrock	04 450 lm/ft	835 80 CRI, 3500 K	04 4'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025423
									EL Standby Battery Pack, Left Side	11025424
					08 8'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025435
									EL Standby Battery Pack, Left Side	11025436
					12 12'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025447
									EL Standby Battery Pack, Left Side	11025448
			07 750 lm/ft	835 80 CRI, 3500 K	04 4'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025425
									EL Standby Battery Pack, Left Side	11025426
					08 8'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025437
									EL Standby Battery Pack, Left Side	11025438
					12 12'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025449
									EL Standby Battery Pack, Left Side	11025450



**4" Recessed Individual**



# SLOTLIGHT LED II

- Ideal for applications in restricted space
- 2,5", 4" or 6" aperture
- Lengths are nominal
- Opal Flush Lens
- Emergency back-up options available

SLEDI	4					P	W	DU		
FIXTURE	WIDTH	MOUNTING	LIGHT LEVEL	LED	LENGTH	OPTIC	COLOR	DRIVER	OPTIONS	ORDERING PART NUMBER
SLEDI SLOTLIGHT LED II Individual Recessed	4 4'	SG Lay-in, 9/16" Slotgrid or Tegular *	04 450 lm/ft	835 80 CRI, 3500 K	04 4'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025427
									EL Standby Battery Pack, Left Side	11025428
					08 8'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025439
									EL Standby Battery Pack, Left Side	11025440
					12 12'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025451
									EL Standby Battery Pack, Left Side	11025452
			07 750 lm/ft	835 80 CRI, 3500 K	04 4'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025429
									EL Standby Battery Pack, Left Side	11025430
					08 8'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025441
									EL Standby Battery Pack, Left Side	11025442
					12 12'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025453
									EL Standby Battery Pack, Left Side	11025454

\* Lay-In fixtures compatible with Armstrong TechZone and USG Logix Ceilings



## SLOTLIGHT LED II

4" Recessed Individual

- Ideal for applications in restricted space
- 2,5", 4" or 6" aperture
- Lengths are nominal
- Opal Flush Lens
- Emergency back-up options available

SLEDI	4					P	W	DU		
FIXTURE	WIDTH	MOUNTING	LIGHT LEVEL	LED	LENGTH	OPTIC	COLOR	DRIVER	OPTIONS	ORDERING PART NUMBER
SLEDI SLOTLIGHT LED II Individual Recessed	4 4'	IW Lay-in, 15/16" Tee*	04 450 lm/ft	835 80 CRI, 3500 K	04 4'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025431
									EL Standby Battery Pack, Left Side	11025432
									-	11025443
			08 8'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025444		
							EL Standby Battery Pack, Left Side	11025444		
							-	11025455		
		12 12'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025456			
						EL Standby Battery Pack, Left Side	11025456			
						-	11025433			
		07 750 lm/ft	835 80 CRI, 3500 K	04 4'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025433	
								EL Standby Battery Pack, Left Side	11025434	
								-	11025445	
08 8'	P Flush Opal			W White	DU 0-10V Dimming Driver 120/277V	-	11025446			
						EL Standby Battery Pack, Left Side	11025446			
						-	11025457			
12 12'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025457					
				EL Standby Battery Pack, Left Side	11025980					
				-	11025457					

\* Lay-In fixtures compatible with Armstrong TechZone and USG Logix Ceilings