



SLOTLIGHT LED II

6" Recessed Individual

- Ideal for applications in restricted space
- 2,5", 4" or 6" aperture
- Lengths are nominal
- Opal Flush Lens
- Emergency back-up options available

SLEDI	4					P	W	DU		
FIXTURE	WIDTH	MOUNTING	LIGHT LEVEL	LED	LENGTH	OPTIC	COLOR	DRIVER	OPTIONS	ORDERING PART NUMBER
SLEDI SLOTLIGHT LED II Individual Recessed	6 6'	EA Flangeless - After Sheetrock	04 450 lm/ft	835 80 CRI, 3500 K	04 4'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025464
									EL Standby Battery Pack, Left Side	11025466
					08 8'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025496
									EL Standby Battery Pack, Left Side	11025497
					12 12'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025484
									EL Standby Battery Pack, Left Side	11025485
			07 750 lm/ft	835 80 CRI, 3500 K	04 4'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025468
									EL Standby Battery Pack, Left Side	11025469
					08 8'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025498
									EL Standby Battery Pack, Left Side	11025499
					12 12'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025486
									EL Standby Battery Pack, Left Side	11025487



**6' Recessed,
Individual**



SLOTLIGHT LED II

- Ideal for applications in restricted space
- 2,5", 4" or 6" aperture
- Lengths are nominal
- Opal Flush Lens
- Emergency back-up options available

SLEDI	6					P	W	DU			
FIXTURE	WIDTH	MOUNTING	LIGHT LEVEL	LED	LENGTH	OPTIC	COLOR	DRIVER	OPTIONS	ORDERING PART NUMBER	
SLEDI SLOTLIGHT LED II Individual Recessed	6'	SG Lay-in, 9/16" Slotgrid or Tegular*	04 450 lm/ft	835 80 CRI, 3500 K	04 4'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025470	
									EL Standby Battery Pack, Left Side	11025472	
					08 8'	P Flush Opal	W White		DU 0-10V Dimming Driver 120/277V	-	11025500
						EL Standby Battery Pack, Left Side	11025501				
			12 12'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025488			
						EL Standby Battery Pack, Left Side	11025489				
		07 750 lm/ft	835 80 CRI, 3500 K	04 4'	835 80 CRI, 3500 K		P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025473
										EL Standby Battery Pack, Left Side	11025475
						08 8'	P Flush Opal	W White		DU 0-10V Dimming Driver 120/277V	-
							EL Standby Battery Pack, Left Side	11025503			
				12 12'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025490		
							EL Standby Battery Pack, Left Side	11025491			

* Lay-In fixtures compatible with Armstrong TechZone and USG Logix Ceilings



SLOTLIGHT LED II

6' Recessed,
Individual

- Ideal for applications in restricted space
- 2,5", 4" or 6" aperture
- Lengths are nominal
- Opal Flush Lens
- Emergency back-up options available

SLEDI	6					P	W	DU			
FIXTURE	WIDTH	MOUNTING	LIGHT LEVEL	LED	LENGTH	OPTIC	COLOR	DRIVER	OPTIONS	ORDERING PART NUMBER	
SLEDI SLOTLIGHT LED II Individual Recessed	6'	IW Lay-in, 15/16" Tee	04 450 lm/ft	835 80 CRI, 3500 K	04 4'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025477	
								EL Standby Battery Pack, Left Side	11025479		
					08 8'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025504	
						EL Standby Battery Pack, Left Side	11025505				
			12 12'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025492			
						EL Standby Battery Pack, Left Side	11025493				
				07 750 lm/ft	835 80 CRI, 3500 K	04 4'	P Flush Opal	W White	DU 0-10V Dimming Driver 120/277V	-	11025481
							EL Standby Battery Pack, Left Side	11025482			
		08 8'	P Flush Opal			W White	DU 0-10V Dimming Driver 120/277V	-	11025506		
							EL Standby Battery Pack, Left Side	11025507			
		12 12'	P Flush Opal			W White	DU 0-10V Dimming Driver 120/277V	-	11025494		
							EL Standby Battery Pack, Left Side	11025495			

* Lay-In fixtures compatible with Armstrong TechZone and USG Logix Ceilings