



CRAFT MEDIUM FOR TECTON®

CRAFT MEDIUM HIGH BAY LUMINAIRE FOR TECTON®

- Internal cooling ribs for optimum thermal management and prevention of dust accumulation
- Separate lens for each LED with high-precision direction of light and good glare control – UGR < 22 for lower lumen package
- Narrow beam optic illuminates long and high rows of shelves uniformly in warehouses
- Wide beam optic creates an even, rectangular light distribution
- Light weight: 13 lbs
- Ambient operating temperatures between -40° F and +131° F



DELIVERED LUMENS	COLOR TEMPERATURE	COLOR RENDERING	WATTS	UGR
13000 lm	4000 K	CRI 70	100 W	< 22
17000 lm	6500 K	CRI 80	139 W	< 25

Order Code

CRAFTMTEC	2	3	PM	5	WH	U
-----------	---	---	----	---	----	---


1 FIXTURE	CRAFTMTEC
2 LUMENS	13000 13000 Lumens 17000 17000 Lumens
3 CRI/CCT	765 CRI 70, 6500 K 840 CRI 80, 4000 K
4 OPTIC	PM Optics with safety glass cover
5 BEAM	NB Narrow Beam ¹ WB Wide Beam
6 FINISH	WH White
7 DRIVER	U 0-10 V Dimming Driver

1 Available only with 13000 lumen unit


Trunking Order Code

Trunking elements must be ordered separately. Consult TECTON® Trunking specification sheets for order codes.

Light Distribution



Dimensions



Optical Performance

		765		840		Efficacy (lm / W)				
Fixture	Optic	Lumens	Watts	Lumens	Watts	Length	Lumens	765	840	W
CRAFT M	WB	12557	100	12457	100	CRAFT M	WB	126	125	100
	WB	16950	139	16047	139		WB	122	115	139
	NB	12605	100	12505	100		NB	126	125	100

Technical Detail

- 1) Trunking and Adapter:** CRAFT is compatible with the TECTON® System. The fixture is supplied with a TECTON® adapter.

2) Construction: The housing is made of diecast aluminum with a matte white finish. Powder coated internal cooling ribs for optimum thermal management and minimum dust accumulation. A safety glass lens is screwed to the housing in order to protect the optic.

3) Wattage & CCT: The unit is available in 100 W with 13000 lm or 139 W with 17000 lm and in 80+ CRI, 4000 K or 70+ CRI, 6500 K.
- 4) Optic:** The optic is a transparent polymethyl-methacrylate (PM) diffuser that reduces glare and provides high-precision direction of light via separate lens compartments for each LED. A Narrow Beam is offered for focused illumination and a Wide Beam optic for is available for uniform, rectangular illumination without dark spots.

5) Driver: A universal voltage 120/277V driver with integral 0-10V dimming is available. The ambient operating temperature varies from -40° F to +131° F.

6) Life: 50,000 hours rated life. L85 (4000 K), L90 (6500 K).

- 7) Weight:** 13 lbs.

8) Run Length: Maximum length of fixture run per feed:

Maximum Length		
Lumens	120V	277V
13000	18'	42'
17000	13'	30'