



VIVO MEDIUM FOR TECTON

## VIVO

### Medium Track Head for TECTON

- LED track light with excellent color quality
- Optimized for efficient and high-performance accent lighting in shops and salesrooms
- Compatible with TECTON Linear Trunking System
- Passive cooling achieved by innovative thermal design
- Track light head rotates through 360°, pivots through 90°
- Black polycarbonate front ring provides excellent glare control
- Front ring serves for accommodation of various accessories
- Highly specular, iridescence-free reflector made out of aluminized polycarbonate

IBEW UNION MADE

DELIVERED LUMENS	COLOR TEMPERATURE	COLOR RENDERING	WATTS
2800 lm	3000 K 4000 K (MacAdam 3 Step)	CRI 80+	27 W (up to 103 lm/W)



Suitable for dry locations

### Vivo Driver and Trim Order Code

VIVOM	2800	3	4	80	WH	TEC	8
-------	------	---	---	----	----	-----	---

1. FIXTURE	<b>VIVOM</b> Medium Spotlight
2. LUMEN OUTPUT	<b>2800</b> 2800 lm
3. CCT	<b>K30</b> 3000K   <b>K40</b> 4000K
4. BEAM SPREAD	<b>FL</b> Flood (47°)   <b>WF</b> Wide Flood (57°)
5. CRI	<b>80</b> 80 CRI
6. FINISH	<b>WH</b> White
7. ADAPTER	<b>TEC</b> TECTON mounting
8. DRIVER	<b>DUNV</b> 0-10V Dimming, 1%   <b>DAUNV</b> Dali Dimmin, 3%


#### OPTIONAL COMPONENTS (ORDER SEPARATELY)

<b>60700274</b>	Interchangeable reflector, flood
<b>60700278</b>	Interchangeable reflector, wide flood
<b>60700342</b>	Black anti-glare ring
<b>60700343</b>	Soft-outline lens (blur)
<b>60700344</b>	Oval outline lens (50°)
<b>60700345</b>	Interchangeable reflector with high-contrast aperture


### Trunking Order Code

Trunking elements must be ordered separately. Consult Trunking specification sheets for order codes.


Light Distribution



Dimensions



Illuminance at a Distance

47° Flood: 27 W / 80 CRI / 4000 K					57° Wide Flood" 27 W / 80 CRI / 4000 K			
D	FC	L	W		D	FC	L	W
5'	485	2.1'	2.1'		5'	250	3.1'	3.1'
7.5'	215	3.1'	3.1'		7.5'	111	4.6'	4.6'
10'	121	4.2'	4.2'		10'	62	6.2'	4.2'
12.5'	77	5.3'	5.3'		12.5'	40	7.8'	7.3'
15'	53	6.4'	6.4'		15'	27	9.3'	9.3'
CBCP: 12135   Lumens: 2800 LPW: 103 lm/W					CBCP: 6254   Lumens: 2800 LPW: 103 lm/W			

Multipliers

CCT and CRI		
CRI	CCT	Multiplier
80	3000	0.97
	4000	1.00

Technical Detail

- 1) Trunking and Adapter:** VIVO is compatible with the TECTON system. The fixture is supplied with a TECTON adapter.

**2) Wattage and CCT:** Unit is 27 W, and is available in 3000K and 4000K, with 80 CRI.

**3) Dimming:** Unit is available with 120/277V 0-10V dimming driver (1%), and Dali dimming driver (3%).

**4) Construction:** The housing is made of die-cast aluminum painted white. The trackhead rotates through 360° and pivots through 90°. The optic is a polycarbonate (PC) aluminum sputtered highly specular reflector.

**5) Beam Spread:** Unit is available with Flood (47°) and Wide Flood (57°) beam spread. The beam pattern is clean and symmetric, free of striations with a smooth transition from center beam to outer edge.
- 6) Accessories:** The front cylinder of the housing accommodates for the accessories internally while providing a seamless appearance. The optional components are interchangeable reflectors (Flood distribution, Wide Flood distribution and high-contrast aperture). They can be used together with an anti-glare ring (black) and a soft-outline lens (blur) or an oval outline lens (50°).

**7) Application:** Maximum units per power feed per the table below:

Maximum Units Per Power Feed		
CCT	120V	277V
3000K	53	123
4000K	51	118

**8) Life:** 50,000 hours rated life. L80.

**9) Weight:** 3 lbs.